



10641 Highway 36
Covington, GA
30014

www.sunbeltbuilders.com

t 770.786.3031
f 770.786.3046

CENTRAL PARK RESTROOMS

Vanguard Commercial Flooring
1750 Corporate Drive
Suite 700
Norcross, GA 30093
ph: 678-409-7626
Patti Ross
Patti@vanguard-cf.com

09-6119 Concrete Floor Sealing O&M



CLOSE OUT PACKAGE

PROJECT:

City of Covington – Central Park Restrooms

Submitted By: Patti Ross

**Vanguard Commercial Flooring
1750 Corporate Drive, Suite 700
Norcross, GA 30093
678-409-7626**

patti@vanguard-cf.com

TABLE OF CONTENTS

- 1. 09-6119: EUCLID SUPER AQUA-CURE VOX SEALER**
 - A. PRODUCT DATA**
 - B. SDS**

- 2. JOHNSONITE 4" RUBBER COVE BASE, COLOR: 40, BLACK**
 - A. PRODUCT DATA**
 - B. WARRANTY**
 - C. MAINTENANCE**

1.



SUPER AQUA-CURE VOX

WATER-BASED, HIGH-SOLIDS, LOW ODOR CURE & SEAL
FOR CONCRETE

EUCLID CHEMICAL

PACKAGING

55 gal (208 L) drums
Code: 050Z 55

5 gal (18.9 L) pails
Code: 050Z 05

CLEAN UP

Warm, soapy water
(see "Clean-Up and Removal")

SHELF LIFE

2 years when stored properly

SPECIFICATIONS/COMPLIANCES

- VOC Content: 174 g/L
- AASTM C1315, Type 1, Class B
- ASTM C309, Type 1, Classes A & B
- AASHTO Specification M 148, Type 1, Classes A & B
- Canadian Food Inspection Agency compliant

DESCRIPTION

SUPER AQUA-CURE VOX is a high-solids, water-based acrylic polymer curing and sealing compound. SUPER AQUA-CURE VOX is suitable for use over new and old concrete and performs well on both interior and exterior surfaces. It enables fresh concrete to maintain adequate moisture, seals the surface, and provides an attractive sheen.

PRODUCT CHARACTERISTICS

FEATURES/BENEFITS

- Forms an efficient moisture barrier for optimum curing of concrete
- High solids content permits greater coverage and better durability
- Seals concrete surfaces to help protect against the effects of weathering
- Helps eliminate dusting of new concrete through good surface strength development
- Gives an alternative to solvent-based materials where fumes may be objectionable, undesirable, or non-compliant

COMMON METHODS

- Industrial pump-up sprayer with high solids-nozzle
- Short-nap roller

PRIMARY APPLICATIONS

- Parking decks
- Interior & exterior concrete
- Industrial floors
- Basements & footings
- Walls
- Pavements

APPEARANCE

SUPER AQUA-CURE VOX is a milky white liquid in the container. After application and drying, SUPER AQUA-CURE VOX will slightly darken concrete, and will have a medium-gloss finish. A small test area is strongly recommended to confirm appearance prior to beginning full application.

APPLICATION PROPERTIES

These properties are based on laboratory conditions at 70 °F. Expect variation based on jobsite conditions.

Solids content:	> 25%
Dry to touch:	1 to 2 hours
Recoat:	2 to 4 hours
Foot Traffic:	4 to 6 hours
Wheel Traffic:	6 to 10 hours
Moisture Loss (ASTM C156):	< 0.40 g/m ²

COVERAGE

New Concrete

1st Coat:	300 to 400 ft ² /gal (7.4 to 9.8 m ² /L)
2nd Coat:	400 to 500 ft ² /gal (9.8 to 12.3m ² /L)

Existing Concrete & Re-Sealing

1st Coat:	300 to 400 ft ² /gal (7.4 to 9.8 m ² /L)
2nd Coat:	400 to 500 ft ² /gal (9.8 to 12.3m ² /L)

*Coverage rates are approximations. Actual coverage will vary based on temperature, texture, and substrate porosity.

DIRECTIONS FOR USE

Surface Preparation: For existing concrete, the surface must be clean of any and all surface contaminants, and free of standing water. If applying SUPER AQUA-CURE VOX to previously sealed concrete, call Euclid Chemical to check compatibility. If the chemical makeup of the previous sealer is unknown, a small test section is strongly recommended to check compatibility between SUPER AQUA-CURE VOX and the old sealer. When applying SUPER AQUA-CURE VOX to freshly poured concrete as a cure & seal, the surface bleed water must be allowed to evaporate prior to applying SUPER AQUA-CURE VOX, and the surface must be hard enough as to not be marred during product application.

Mixing: SUPER AQUA-CURE VOX requires no pre-blending prior to use. Euclid Chemical water-based cure & seals, like SUPER AQUA-CURE VOX, are not compatible with Euclid Universal Color Packs or Euco Grip. If use of color or slip-resistant additive is desired, consider using a Euclid Chemical solvent-based cure & seal instead.

Application: Apply at the recommended coverage rate using an industrial pump-up sprayer with a high-solids nozzle and a short-nap roller. Apply sealer uniformly to the concrete using sprayer, then lightly backroll the sealer to ensure even coverage. Maintain a "wet edge" while spraying, and backroll over sprayer lap marks for best appearance. SUPER AQUA-CURE VOX may be applied by roller alone, but extra care must be taken to ensure that the sealer is applied uniformly, and at the proper coverage rate. Re-distribute any puddles or runs before SUPER AQUA-CURE VOX dries. Protect freshly coated surfaces from rain or heavy fog for a minimum of 24 hours after application.

Application of SUPER AQUA-CURE VOX too heavily, in too many successive coats, or in multiple coats from re-sealing too frequently can cause failure to dry completely, bubbling, whitening, peeling, flaking, and ultimately, failure of the product. To prevent over-application, it is good practice to measure the area to be sealed and then measure the corresponding volume of product required based on the coverage rate. In addition, applying SUPER AQUA-CURE VOX in hot weather/direct sunlight or onto a hot surface can cause bubbling.

For additional guidance in applying Euclid Chemical curing and sealing compounds, visit our website to see an instructional video on the procedure.

CLEAN-UP AND REMOVAL

Tools and equipment may be cleaned with warm, soapy water immediately following use. Clean drips and overspray with warm, soapy water while still wet. Run warm, soapy water through spray equipment to remove residual materials and prevent clogging of nozzle in future use. If not cleaned immediately, the sealer may leave an unwanted residue on painted surfaces, glass, or wood.

Hardened/dried SUPER AQUA-CURE VOX may be removed with a strong solvent such as xylene/xylol or MEK (always follow package directions and warning labels). EUCO CLEAN & STRIP is a citrus-based stripper that may also be used to remove this product. Alternatively, the product can be removed by sand blasting or other mechanical means.

PRECAUTIONS/LIMITATIONS

- Store SUPER AQUA-CURE VOX indoors, protected from moisture, at temperatures between 50 °F and 90 °F (10 °C and 32 °C)
- Surface and ambient temperature during coating applications should be between 45 °F and 95 °F (7 °C and 35 °C)
- Material temperatures should be at least 50 °F (10 °C) and rising
- Do not apply SUPER AQUA-CURE VOX to frost-filled or frozen substrates
- Do not apply SUPER AQUA-CURE VOX in hot direct sunlight
- Do not apply SUPER AQUA-CURE VOX over bleed water or free-standing water
- Do not apply SUPER AQUA-CURE VOX if rain or heavy fog is expected within 24 hours of application
- Do not thin SUPER AQUA-CURE VOX
- SUPER AQUA-CURE VOX is not resistant to gasoline or other automotive fluids
- SUPER AQUA-CURE VOX will enhance color and darken substrates
- Excessive build up of SUPER AQUA-CURE VOX or puddling of the product during application can lead to failure to dry completely, bubbling, whitening, peeling and/or flaking of the sealer, and discoloration of the concrete
- Applying thicker than recommended, applying in cool/cold weather, prolonged exposure to moisture (high humidity, rain), or lack of air flow may result in the sealer remaining soft/wet/tacky for longer than the times found on this data sheet
- When floor covering adhesives will be used following SUPER AQUA-CURE VOX application, a test area is recommended to ensure compatibility of the adhesive with SUPER AQUA-CURE VOX
- Application of a test area is strongly recommended to confirm final appearance and texture of the product with the end user
- In all cases, consult the product Safety Data Sheet before use

Rev. 03.22

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.

SAFETY DATA SHEET

1. Identification

Material name: SUPER AQUA-CURE VOX
Material: 050Z 55

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY
19218 REDWOOD ROAD
CLEVELAND OH 44110
US

Contact person:	EH&S Department
Telephone:	216-531-9222
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A

Unknown toxicity - Health

Acute toxicity, oral	89.01 %
Acute toxicity, dermal	88.96 %
Acute toxicity, inhalation, vapor	99.94 %
Acute toxicity, inhalation, dust or mist	96.29 %

Label Elements

Hazard Symbol:



Signal Word: Warning

Hazard Statement: Causes serious eye irritation.

Precautionary Statements

Prevention: Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Glycol ether solvent	112-34-5	5 - 10%
Ethanolamine	141-43-5	0.5 - 1.5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store away from incompatible materials. Store in original tightly closed container.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
-------------------	------	-----------------------	--------



Glycol ether solvent - Inhalable fraction and vapor.	TWA	10 ppm	US. ACGIH Threshold Limit Values (03 2013)
Ethanolamine	TWA	3 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	6 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	3 ppm 6 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Glycol ether solvent - Inhalable fraction and vapor.	TWA	10 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes.

9. Physical and chemical properties**Appearance**

Physical state: liquid

Form: liquid

Color: White

Odor: Mild

Odor threshold: No data available.

pH: 9 - 11

Melting point/freezing point: No data available.

Initial boiling point and boiling range: 100 °C 212 °F

Flash Point: > 93 °C > 200 °F(Tag closed cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Strong acids. Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
-------------	--------------------

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 9,752.13 mg/kg

Dermal

Product: ATEmix: 2,756.18 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Glycol ether solvent in vivo (Rabbit): Slightly irritating Experimental result, Key study

Ethanolamine in vivo (Rabbit): Corrosive Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Glycol ether solvent Rabbit, 24 - 72 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

Germ Cell Mutagenicity**In vitro****Product:** No data available.**In vivo****Product:** No data available.**Reproductive toxicity****Product:** No data available.**Specific Target Organ Toxicity - Single Exposure****Product:** No data available.**Specific Target Organ Toxicity - Repeated Exposure****Product:** No data available.**Aspiration Hazard****Product:** No data available.**Other effects:**

No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**Glycol ether solvent LC 50 (Bluegill (*Lepomis macrochirus*), 96 h): 1,300 mg/l MortalityEthanolamine LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 1,810 - 2,370 mg/l Mortality**Aquatic Invertebrates****Product:** No data available.**Chronic hazards to the aquatic environment:**



EUCLID CHEMICAL

Version: 3.0
Revision Date: 02/06/2018

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Glycol ether solvent Log Kow: 0.56

Ethanolamine Log Kow: -1.31

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Styrene	1000 lbs.
2-Propanol	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Glycol ether solvent	
2-Butoxyethanol (Glycol ether)	
Styrene	1000 lbs.
2-Propanol	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Glycol ether solvent	10000 lbs
Ethanolamine	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
Glycol ether solvent

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

US State Regulations**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Styrene	Carcinogenic.
Styrene	Carcinogenic. 04 2016

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Glycol ether solvent

US. Massachusetts RTK - Substance List**Chemical Identity**

Styrene

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Glycol ether solvent

US. Rhode Island RTK**Chemical Identity**

Glycol ether solvent

International regulations**Montreal protocol**

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:Regulatory VOC (less water and
exempt solvent) : 174 g/l

VOC Method 310 : 6.26 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision
--

Revision Date: 02/06/2018

Version #: 3.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

2.



Traditional Wall Base

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Thermoplastic Wall Base

1.2. Manufacturer:

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkett.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Traditional Wall Base is manufactured from a proprietary rubber and vinyl formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861, Type TV (Thermoplastic Vinyl) and TP (Thermoplastic Rubber), Group 1 (solid), Style A and B, Standard Specification for Resilient Wall Base.

1.3.2. Styles/Physical Characteristics:

Rubber Wall Base

- **Traditional:** DC-XX with toe (coved) or DCT-XX for toeless (straight), 0.125" (3.17 mm) thickness, 2-1/2" (6.35 cm), 4" (10.16 cm), 4 1/2" (11.4 cm) or 6" (15.24 cm) height

Available in 4' (1.22 m) straight lengths and 120' (36.58 m) coiled lengths. The 6" (15.24 cm) high profile available in 4' (1.22 m) straight lengths and 100' (30.48 m) coiled lengths

- **Wall Art:** WA-XX w/toe (coved), 0.125" (3.17 mm) thickness, 4" (10.16 cm) height

Available in 4' (1.22 m) straight lengths only

- **Inside and Outside Corners** available with 4" (10.16 cm) returns packaged 25 per carton, add LIC (Inside corners) or LOC (Outside corners)

Vinyl Wall Base

- **Traditional:** CB-XX with toe (coved) or CBT-XX toeless (straight), 0.125" (3.17 mm) or 0.080" thickness, 2-1/2" (6.35 cm), 4" (10.16 cm), or 6" (15.24 cm) height

Cartons size: Available in 4' (1.22 m) straight lengths and 120' (36.58 m) coiled lengths. The 6" (15.24 cm) high profile available in 4' (1.22 m) straight lengths and 100' (30.48 m) coiled lengths

- **Inside and Outside Corners** available with 4" (10.16 cm) returns packaged 25 per carton, add LIC (Inside corners) or LOC (Outside corners)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in ASTM F-1861.

2.2. **Flexibility:** Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.

2.3. **Chemical resistance** (ASTM F 925): Passes – 5% acetic acid, 70% isopropyl alcohol, mineral oil, 5% sodium hydroxide solution, 5% hydrochloric acid solution, 5% sulfuric acid solution, 5% household ammonia solution, and 5.25% household bleach solution

2.4. **Resistance to light** (ASTM F 1515): $\Delta E < 8$

2.5. Fire Resistance:

Vinyl Wall Base

ASTM E 648 (NFPA 253): Critical Radiant Flux – Class I

Rubber Wall Base

ASTM E 648 (NFPA 253): Critical Radiant Flux – Class I

2.6. CAN/ULC-S102.2:

Vinyl Wall Base

FSR 140 / SDV 330

Rubber Wall Base

FSR 165 / SDV 345

3. AVAILABILITY AND COST

For availability and cost contact authorized Tarkett distributors nationwide.

4. INSTALLATION

4.1. See Tarkett wall base installation instructions for complete details.

4.2. Adhesives:

- **Tarkett 960 Cove Base Adhesive** (Porous surfaces):

Application: 1/8" x 1/8" x 1/8" square notched trowel

Approximate coverage:

2 1/2" high – 300 to 350 linear feet/gallon

4" high – 200 to 250 linear feet/gallon

6" high – 100 to 150 linear feet/gallon

- **Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush or roller

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916

info@tarkettna.com

www.tarkett.com



5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to the Rubber Vinyl Wallbase Installation & Maintenance instructions for full details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (800) 899-8916 or E-mail:

Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. LIMITED WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor

Tarkett North America

Technical Services Department

30000 Aurora Road





















Solon, Ohio 44139


800.899.8916

info@tarkettna.com

www.tarkett.com

Solid colors

							
08 Icicle W	24 Grey Haze WG	55 Silver Grey WG	32 Pebble WG	460 Cotton W	27 Mist WG	TG5 Macadamia WG	150 Wetlands
							
29 Moon Rock WG	48 Grey WG	29 Charcoal WG	TA4 Gateway WG	50 White W	469 Mystify CG	WG2 Stone Cottage WG	281 Grizzly CB
							
21 Platinum CG	38 Pewter CG	28 Medium Grey CG	71 Storm Cloud CG	VK7 Mt Rainier WG	199 Dockside WG	TG6 Mink WG	197 Shaded WG
							
01 Snow White W	22 Pearl CB	31 Zephyr CB	80 Fawn CB	TB3 Ivory CG	23 Vapor Grey CG	TG5 Shark Fin CG	TG3 Iron Mountain CG
							
11 Canvas WB	49 Beige WB	TA8 Welsh Castle CB	283 Toast	VM1 White Slipper W	TA5 Colonial Grey CG	262 Drizzle CG	VL4 Cod Metal CG
							
09 Clay WB	45 Sandalwood WB	76 Cinnamon	47 Brown	TG1 Snowbound W	VK8 Sandstorm CB	VL2 Whispering Mist CB	VL1 Harvest Time CB
							
TB1 Peppercorn	167 Fudge	44 Dark Brown B	63 Burnt Umber B	121 Cement CB	TA3 Castaway CB	280 Shoreline	101 Seaweed
							
86 Hunter Green	18 Navy Blue	TA6 Bedrock CG	40 Black B	68 White Sand W	194 Antique White W	125 Silk WB	461 Wicker WB

			
79 Bone White W	34 Almond W	TA1 Tannery	130 Sisal

COLORMATCH®

METALLIC COLORS

We know that color is crucial to the craft of design. That's why we offer easy color coordination, precise color matching, and inspiring palettes to spark your creativity. With our best-in-class service levels and rigorous manufacturing and quality standards, experience color made right with Johnsonite.

ColorMatch®: Perfectly matched flooring and accessories, made easy. ColorMatch is a designer palette of 32 colors available across all Johnsonite product types, with no dye lots... ever! We guarantee these colors will match year after year, product after product.

Color customization: Don't see the exact color you need? Let us create it for you! We offer painless color customization across all our products, with quick lead times and low minimums. Our seasoned color experts will work with you to achieve your vision. Simply contact your local Tarkett representative to get started.

Color Foundations®: It's easy to coordinate Johnsonite products with a wide range of flooring choices from the Tarkett portfolio. Color Foundations gives you six neutral palettes that pair popular Johnsonite colors with hundreds of flooring options for Soft Surface to Resilient. We've done the color- coordination for you. Just pick your palette and go!

Palette Key: WB (Warm Beige), CB (Cool Beige), WG (Warm Grey), CG (Cool Grey), B (Black), W (White)

All colors shown in this card, including chips and photographs, approximate the actual flooring colors as accurately as possible.

Limited Warranty

SECTION	PRODUCT TYPE	JOHNSONITE BRAND PRODUCT LINES
1	Rubber Sheet Flooring	Replay® Rolls
2	Compression Molded Rubber Tile	Circulinity™; CorkTones™; Defiant™; Color Splash; Mesto Configurations™; Minerality™; Organics; Prima® Olio® and Marbleized; Replay® Tiles; Solid Color Rubber Tile; Tactile Walking Surface Indicators; Terra-Turf®; Triumph and Inertia™
3	Stairwell Management	Rubber or Vinyl Stair Treads, Nosings, Risers, Stringers; Tactile Warning Surface, and Safe-T-First®
4	Finishing Borders (Wall Base) Finishing Accessories	BaseWorks®; Masquerade®; Millwork®; Perceptions®; TightLock®; Traditional Rubber or Vinyl; Safe-T-First®; Vent Cove; and Transitions
5	Vinyl Sheet and Tile Flooring	A: iQ™ Optima®; iQ™ Granit™; iQ™ Granit™ SD; Granit™ Safe.T; iQ Eminent™; iQ™ Eminent Unisense; iQ Granit Sense B: Acczent®; Acczent Flourish C: Aria™; Melodia™; Performa™; Training®; iQ™ Optima® Acoustic; iQ Eminent Acoustic iQ Granit Acoustic
6	Vinyl Composition Tile	Tarkett VCT II
7	Linoleum Sheet Flooring	LinoFloor xf2™; LinoWall xf2™
8	Luxury/Solid Vinyl Tile and Plank	A: Adaptt™ B: Event+; iD Latitude + Tectonic™; iD Tilt HiT; Victory® C: Contour + Tectonic™; Even Plane D: Collective Pursuit
9	Underlayment	SureStart™ Underlayment

Tarkett Warranty Overview

Tarkett is pleased to offer the world's most-integrated, high-performance flooring system, bringing together design, function, and safety, leading to enhanced productivity in high-performance environments. All Tarkett products are warranted against manufacturers' defects to ensure high standards of quality, performance, and aesthetics.

Limited Warranty Information

Section 1: Rubber Sheet Flooring

Limited 5-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of five (5) years of Commercial use that rubber sheet flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-5).

Tarkett warrants that the products will not wear through for the warranty period of five (5) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.



Section 2: Compression Molded Rubber Tile

Limited 5-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of five (5) years of Commercial use that molded rubber tile flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-5).

Tarkett warrants that the products will not wear through for the warranty period of five (5) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 3: Rubber or Vinyl Stair Treads

Limited 5-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of five (5) years of Commercial use that rubber or vinyl stair tread products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-5).

Section 4: Finishing Borders (Wall Base & Accessories)

Limited 2-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of two (2) years of Commercial use that rubber or vinyl wall base and/or accessory products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2).

Section 5A: Vinyl Sheet and Tile Flooring

Limited 20-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of twenty (20) years of Commercial use that vinyl sheet and/or tile flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2-3); Material and 25% Reasonable Labor Costs (Year 4-5); Material Only (Years 6-10); 50% Material Only (Years 11-15); and 25% Material Only (Years 16-20).

Tarkett warrants that the products will not wear through for the warranty period of twenty (20) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 5B: Vinyl Sheet and Tile Flooring

Limited 15-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of fifteen (15) years of Commercial use that vinyl sheet flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2-3); Material Only (Years 4-10); 50% Material Only (Years 11-15).

Tarkett warrants that the products will not wear through for the warranty period of fifteen (15) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 5C: Vinyl Sheet and Tile Flooring

Limited 10-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of ten (10) years of Commercial use that vinyl sheet and/or tile flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2-3); and Material Only (Years 4-10).

Tarkett warrants that the products will not wear through for the warranty period of ten (10) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 5D: Vinyl Sheet and Tile Flooring

Limited 5-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of five (5) years of Commercial use that vinyl sheet and/or tile flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2-3); and Material Only (Years 4-5).

Tarkett warrants that the products will not wear through for the warranty period of five (5) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 6: Vinyl Composition Tile

Limited 5-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of five (5) years of Commercial use that vinyl composition tile and plank flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the

defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-5).

Tarkett warrants that the products will not wear through for the warranty period of five (5) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 7: Linoleum Sheet Flooring

Limited 10-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of ten (10) years of Commercial use that linoleum sheet flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-10).

Tarkett warrants that the products will not wear through for the warranty period of ten (10) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 8A: Luxury Tile and Plank

Limited 10-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of ten (10) years of Commercial use that luxury tile and plank flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-10).

Tarkett warrants that the products will not wear through for the warranty period of ten (10) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 8B: Luxury Tile and Plank

Limited 20-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of twenty (20) years of Commercial use that luxury tile and plank flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); Material Only (Years 3-10); 50% Material Only (Years 11-15); and 25% Material Only (Years 16-20).

Tarkett warrants that the products will not wear through for the warranty period of twenty (20) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 8C: Luxury Tile and Plank

Limited 25-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of twenty-five (25) years of Commercial use that luxury tile and plank flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); Material Only (Years 3-10); 50% Material Only (Years 11-15); and 25% Material Only (Years 16-25).

Tarkett warrants that the products will not wear through for the warranty period of twenty-five (25) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 8D: Luxury Tile and Plank

Limited 15-Year Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of fifteen (15) years of Commercial use that luxury tile and plank flooring products conform to written specifications and are free of manufacturing defects, subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects prior to installation; otherwise, this warranty will not apply. If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge. If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2-3); Material Only (Years 4-10); 50% Material Only (Years 11-15).

Tarkett warrants that the products will not wear through for the warranty period of fifteen (15) years of Commercial use. For claims based on wear-through, the customer must notify Tarkett and permit an inspection of the flooring. If Tarkett determines that the original flooring is worn through, Tarkett will replace or repair the worn flooring at its own cost; however, labor costs will be the customer's responsibility except as provided on the prorated basis described in the prior paragraph.

Section 9: Underlayment

Limited 10-Year Light Commercial Warranty for Manufacturing Defects: Tarkett warrants from the date of purchase for a period of ten (10) years of Light Commercial use of SureStart™ underlayment with approved Tarkett LVT products, subject to subfloors being prepared & meeting Tarkett Installation Instruction guidelines and subject to the terms and conditions specified herein.

The customer must notify Tarkett of any obvious visual defects or concerns prior to install; otherwise, this warranty will not apply.

If the defect is found and Tarkett is notified in writing prior to installation, Tarkett will replace any defective product, at no charge.

If the customer believes the product to be defective after installation, the customer must promptly notify Tarkett and permit an inspection of the product. If, upon inspection, Tarkett determines that the product is defective, Tarkett will replace or repair the defective product at its own cost, subject to the limitations in this warranty, and prorated as follows: Material and 100% Reasonable Labor Costs (Year 1); Material and 50% Reasonable Labor Costs (Year 2); and Material Only (Years 3-10).

All Tarkett Commercial Products:

This Limited Warranty applies only for products installed, used, and maintained according to the written recommendations and specifications provided at the time of material purchase.

Warranty Claim Procedure

To be eligible for replacement under this warranty, the customer must file a claim by giving Tarkett written notice of the defect. This notice must be filed immediately, but in no event more than 10 days following discovery of the defect. Notice shall be given to Tarkett at its corporate address of 30000 Aurora Road, Solon, Ohio 44139.
Phone: (800) 899-8916; Fax: (440) 543-5774.

If defective product has been discontinued or is otherwise unavailable, Tarkett reserves the right to select and supply the customer with Tarkett replacement flooring, similar in quality and quantity to the material claimed to be defective.

Warranty Exclusions

The Tarkett Limited Warranty does not apply to:

- The exact matching of shade, color, or mottling.
- Tears, burns, cuts or damage due to improper installation or use or improper cleaning agents and maintenance methods.
- Labor costs outside of prorated schedule defined in the warranty.
- Sales of non-first quality materials, i.e., "seconds," "off goods" or other irregular flooring. Such non-first quality materials are sold "AS IS."
- Issues associated with the use of adhesives other than those recommended by Tarkett.
- Issues caused by moisture or alkali in the subfloor.
- Issues of discoloration or staining associated with subfloor contamination or markings that bleed through the flooring material.
- Problems caused by installation, uses and maintenance that are contrary to Tarkett's specifications, recommendations, or instructions.
- Material installed with obvious defects not notified to Tarkett prior to installation.
- Exterior installations – Tarkett products are designed for interior applications only.
- Fading and/or discoloration resulting from heavy sunlight penetration and ultraviolet ray exposure from direct or glass-filtered sunlight.
- Damage to flooring products caused by high or spiked heels, casters, or furniture rests. Some rolling-type casters on furniture or appliances may damage resilient flooring. Warranty as to the suitability of the factory-installed casters rests with the furniture or appliance manufacturers.
- Damage to flooring products from pallet jack and tow-motor traffic.
- Premature wear or deterioration from spikes and skate blade exposure.
- Variations in color or embossing between products, photography, or printed color illustrations.
- Installation of Tarkett flooring in work or commercial areas exposed to oil and grease or animal fats. Defiant™ Oil and Grease-Resistant Rubber tiles are recommended in such situations.
- Additional expense associated with overtime, replacing or moving appliances or furniture, business interruptions, loss of use or other related costs associated with the replacement of the flooring.
- Shifting, cracking, or movement of the substrate or foundation.
- Hydrostatic pressure, flooding, standing water or moisture on the surface of the substrate.
- Issues related to exposure to heavy rolling loads or site construction related damage.

Warranty Disclaimer

- EXCEPT AS STATED HEREIN, TARKETT MAKES NO WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED. ALL IMPLIED WARRANTIES WHICH MAY ARISE BY LAW, IMPLICATION OF LAW OR APPLICATION OF COURSE OF DEALING, PERFORMANCE OR USAGE OF TRADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY DISCLAIMED AND EXCLUDED. ANY ORAL STATEMENTS ABOUT THE PRODUCTS DESCRIBED HEREIN ARE NOT WARRANTIES, SHOULD NOT BE RELIED UPON BY BUYER, DO NOT FORM ANY PART OF THE BASIS OF THE BARGAIN, AND ARE NOT PART OF THIS OR ANY OTHER LIMITED WARRANTY. NO AGENT, DISTRIBUTOR OR REPRESENTATIVE OF TARKETT, EXCEPT AN AUTHORIZED OFFICER OF TARKETT, SHALL HAVE AUTHORITY TO AGREE TO ANY TERM, CONDITION OR PROVISION INCONSISTENT HERewith OR NOT CONTAINED HEREIN. IN NO EVENT SHALL TARKETT BE LIABLE TO BUYER FOR INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, DAMAGES OR LOSS OF PROFIT ARISING OUT OF OR RELATING TO ANY BREACH OF THIS WARRANTY, REGARDLESS OF THE LEGAL OR EQUITABLE THEORY (CONTRACT, TORT, OR OTHERWISE) UPON WHICH THE CLAIM IS BASED.
- These warranties provide specific legal rights; these and other rights may vary from state to state.

Tarkett North America

30000 Aurora Road
Solon, Ohio 44139
800.899.8916

[tarkett.com](https://www.tarkett.com)

©Tarkett North America 03/2024



INSTALLATION & MAINTENANCE INSTRUCTIONS

RUBBER & VINYL TRADITIONAL WALL BASE

BaseWorks™, Masquerade® (Cove Profile Only), Perceptions™, Traditional Duracove® 1/8" (Type TP), & Traditional 1/8" & .080" (Type TV)

INTRODUCTION

These instructions are written as a guide to be used by professional installers when installing Tarkett products. These instructions, combined with our adhesives and flooring products, create a system. Utilizing this system will ease the installation process and provide the customer with a completed product that will perform to its intended purpose. Always visit www.tarkett.com for the most current installation and maintenance instructions. Technical videos and tip sheets are also available. Contact Tarkett Technical Services at (800)-899-8916 with any questions.

HANDLING AND STORAGE

Tarkett cannot accept responsibility for any loss or damage that may result due to processing or working conditions and/or workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.

NOTE: Tarkett recommends that the installation of new flooring material not be performed until all the other trades have completed their work. Proper precautions must be taken during and after the installation process to avoid damage to the newly installed flooring.

STORING ALL PRODUCTS & ADHESIVES	PRE-INSTALLATION
Stack cartons squarely on top of one another, do not over stack cartons and protect corners from damage by tow-motors and other traffic. NOTE: Do not flex, bend, or stand cartons on end. Never double stack pallets.	Room temperature must be maintained between 65°F (18.3°C) and 85°F (29.4°C) with ambient relative humidity between 40% and 60% for 48 hours prior to, during the entire installation, and after installation. NOTE: Permanent, operational HVAC systems are highly recommended. If alternate system is utilized, it must provide proper control of both temperature and humidity for the above stated time durations.
Store on a dry, flat, level surface.	Site-condition flooring, accessories, and adhesives 48 hours prior to installation. The location selected for site-conditioning must be either the room where the flooring will be installed or have similar ambient temperature and relative humidity readings as the room where the flooring will be installed.
Maintain temperature between 65°F (18.3°C) and 85°F (29.4°C).	In areas exposed to intense or direct sunlight, protect the product by covering the light source during site-conditioning, installation, and adhesive curing periods. If exposure to intense or direct sunlight will continue after the installation and adhesive curing period, refer to adhesive chart below.
Maintain relative humidity between 40 – 60%.	Inspect all flooring material to verify accuracy of order as well as for any damage, visual defects, and satisfactory color match. Notify an authorized Tarkett Distributor or Representative prior to installation if any defects are found. NOTE: Tarkett will not pay for labor or material costs claimed on installed materials with visual defects.
Tarkett products are recommended for installation in Indoor, Climate-Controlled spaces only. NOTE: Exposure to excessive UV light can result in fading, degradation, and/or color variation.	Care must be taken not to pull the wall base excessively when removing it from the carton or when unrolling coils. The wall base will not shrink, but it will relax to its original length, if stretched. To assist with the installation process, coils should be unrolled and allowed to relax for a minimum of 24 hours prior to installation.

GENERAL SUBSTRATE PREPARATION

An **adhesive bond test** must be performed per **ASTM F3311 Standard Practice for Mat Bond Evaluation of Performance and Compatibility for Resilient Flooring System Components Prior to Installation** and using the actual flooring materials and adhesive to be installed. The test areas must be a minimum of 36" piece and remain in place for at least 72 hours and then evaluated for bond strength to the substrate.

A **porosity test** must be performed on the substrate to determine which installation method (porous or non-porous) will be required. Apply a saturated sponge or cloth to the substrate surface and remove. If moisture remains beaded on the surface, this substrate would be considered non-porous. If moisture is absorbed, this substrate would be considered porous. **NOTE: Epoxy paints, FRP, fiberglass, melamine, and other non-porous wall coverings will require the use of Tarkett 946 Premium Contact Adhesive.**

Substrate Construction	Requirements
All Substrates	Permanently dry, flat, clean, smooth, and structurally sound NOTE: Do not install Wall Base over vinyl wall coverings.
	Never install Wall Base on surfaces that will be exposed to drastic temperature changes or moisture.
	Free of all dust, loose particles, solvents, paint, grease, oil, wax, alkali, sealing/curing or parting compounds, old adhesive, and any other foreign material, which could affect the installation and adhesive bond to the substrate. All substrate contaminants must be mechanically removed prior to the installation of the flooring DO NOT use liquid solvents or adhesive removers DO NOT use oil-based sweeping compounds NOTE: Permanent and non-permanent markers, pens, crayons, paint, or similar marking tools used to mark the substrate or back of the resilient flooring material will cause migratory staining that is not covered by the warranty.

(All Substrates Cont.)	Minimum substrate temperature must be 60°F (15.6°C) and must be within 5°F (2.8°C) of ambient temperature
	Substrate temperature must be a minimum of 10°F (5.6°C) higher than the dew point temperature NOTE: Dew point calculators are available online. If the substrate is not 10°F (5.6°C) above the dew point, contact Technical Services at (800) 899-8916
	Fill all depressions, dormant cracks, and other surface irregularities with a good quality patching compound appropriate for this purpose.
	DO NOT install Tarkett products over expansion and other moving joints in the substrate. These joints must be respected and should not be filled with products that are not intended for that purpose. Contact an expansion joint cover manufacturer to meet specific substrate conditions.
Ceramic Wall	Thoroughly sand to remove all glaze and wax
	Remove or replace all loose tiles and clean the grout lines
	Use a good quality, cement-based leveling compound to fill all grout lines and other depressions
Steel NOTE: Follow all non-porous installation instructions	Mechanically abrade to assist with adhesive bond
	Fully clean to remove all dirt, rust, and other contaminants
	Prime with a rust inhibitive primer

INSTALLATION

- Adhesive Application:** See adhesive chart below and follow adhesive label instructions for proper use.
- Installation Procedures:**
 - Allow coiled wall base to lay flat for at least 24 hours, between 65° and 85°F (18.3° and 29.4°C) with HVAC system operating, prior to installation.
 - For installations on porous wall surfaces, apply Tarkett 960 Wall Base Adhesive to the ribbed surface (back) of the wall base with a 1/8" square-notched trowel. The adhesive should cover 80% of the back surface. Leave a 1/4" (6.35mm) uncovered space at the top of the wall base to prevent the adhesive from oozing onto the wall above the base when installed.
 - For installations on non-porous wall surfaces (i.e.: metal, epoxy paint, ceramics, etc.) apply Tarkett 946 Premium Contact Adhesive to both the wall surface and the back of the wall base. Allow adhesive to thoroughly dry to the touch. **NOTE: Once contact is made to the wall surface, the wall base cannot be moved.**
 - Dried adhesive may require the use of denatured alcohol (methyl hydrate) or 70% isopropyl alcohol applied to a clean white cloth. (Follow manufacturer's precautions when using these chemicals.)

CORNER INSTALLATION

- Factory Made Corners (NOT Available for Masquerade):**
 - Install factory made corners before installing wall base.
 - Trowel adhesive to ribbed back of wall base corner.
 - Position corner in place and roll to ensure proper adhesive bond.
 - Attention should be given to a tight and even fit to the corner.

NOTE: Tarkett 946 Premium Contact Adhesive may be used to ensure a faster setup at the corner.
- Field-Made Inside Corners:**
 - Install wall base and terminate into the corner.
 - Position another piece of wall base on opposing wall, without adhesive, approximately 1" from the installed piece.
 - Utilize dividers; place one pin at the top of the installed piece and one pin at the top of the uninstalled piece. Carefully, move the dividers downward in a straight vertical motion, allowing the pin of the dividers to follow the profile of the installed piece. At the same time, place adequate pressure on the pin to transfer and/or scribe the profile onto the surface of the uninstalled piece.
 - Use a utility knife to cut the scribe line on the uninstalled wall base, apply adhesive, and position the trimmed section into place.
- Field-Made Outside Corners**
 - Stop application of adhesive to wall base approximately 18" (45cm) from the outside corner of the wall.
 - Position the wall base at the corner and pencil line the back of the wall base where the bend is required.
 - Lay the wall base on the floor with the backup. Utilizing a top-set or pull-type gouge tool, make a shallow notch along the pencil line.
 - Note:** The notch depth should not exceed one-quarter the total thickness of the wall base.
 - Reposition the wall base corner on the wall. The corner of the wall should fit snugly into the notched recess on the back of the wall base.
 - Apply adhesive and roll firmly into place.

NOTE: Tarkett 946 Premium Contact Adhesive may be used to ensure a faster setup at the corner.

ADHESIVE CLEAN UP

Excess adhesive should be removed during the installation process.

960™ Wall Base Adhesive, 946™ Premium Contact Adhesive

- Use a clean white cloth dampened with water to remove wet adhesive from floor covering and tools.
- Dried adhesive may require the use of denatured alcohol (methyl hydrate) or 70% isopropyl alcohol applied to a clean white cloth. (Follow manufacturer's precautions when using these chemicals.)

MAINTENANCE

1. Wait 72 hours after installation before performing initial cleaning.
2. A regular maintenance program must be started after the initial cleaning.
3. Tarkett Resilient Wall Base is maintained with regular wiping using a wet, clean, soft, white cloth.
4. A mild detergent may be added to the water.
5. Coarse scrubbing media or harsh cleaning chemicals may damage the surface of the wall base.

ADHESIVE SELECTION CHART

Only Tarkett adhesives are recommended for use with Tarkett products. When used as recommended, Tarkett adhesives are guaranteed by the limited warranty of the flooring product.

A porosity test must be performed on the substrate to determine which installation method (porous or non-porous) will be required. Apply a saturated sponge or cloth to the substrate surface and remove. If moisture remains beaded on the surface, this substrate would be considered non-porous. If moisture is absorbed and a darkened spot appears on the wall, this substrate would be considered porous. **NOTE: Epoxy paints, FRB, fiberglass, melamine, and other non-porous wall coverings will require the use of Tarkett 946 Premium Contact Adhesive.**

Products	Adhesive	Application and Coverage		Moisture / pH Limits			Notes
		Porous	Non-Porous	RH%	CaCl ₂	pH	
Resilient Wall Base	960 Wall Base Adhesive	<u>1/8 x 1/8 x 1/8 SQ</u> Per Gallon: 2.5" = 300-350 lf. 3" = 275-325 lf. 3.5" = 230-280 lf. 4" = 200-250 lf. 4.5" = 175-225 lf. 6" = 100-150 lf.	USE 946 PREMIUM CONTACT ADHESIVE	N/A	N/A	N/A	POROUS ONLY
Resilient Wall Base	946 Premium Contact Adhesive	Applied with Brush or Roller		N/A	N/A	N/A	Coverage based on both sides
		1 qt. unit: 2.5" = 115-173 lf. 3" = 96-144 lf. 3.5" = 81-123 lf. 4" = 72-108 lf. 4.5" = 64-96 lf. 6" = 48-72 lf.					
		1 gal. unit: 2.5" = 692-1034 lf. 3" = 576-860 lf. 3.5" = 493-736 lf. 4" = 432-646 lf. 4.5" = 384-573 lf. 6" = 288-430 lf.					

Tarkett North America
Technical Services Department
30000 Aurora Road
Solon, OH 44139
800.899.8916
info@tarkettna.com
www.tarkett.com