



10641 Highway 36
Covington, GA
30014

www.sunbeltbuilders.com

t 770.786.3031
f 770.786.3046

FACTORY SHOALS PARK

Carnes Contract Floors
5238 Royal Woods Parkway
Suite 160
Tucker, GA 30084
ph: 770-934-0083
Mohamed Johar
mjohar@carnescontractfloors.com

09-6723 Flooring Warranties

Daltile 1-Year Limited Warranty

Daltile warrants that manufactured products will be free from defect for a period of one year from date of purchase. Defect is defined as a shortfall in the product to perform to Daltile specifications as disclosed in product literature, within industry-allowable tolerances as set forth in standard, national industry protocols. **THIS ONE-YEAR EXPRESS WARRANTY IS THE SOLE WARRANTY EXTENDED AND REPLACES ANY STATUTORY WARRANTIES TO THE MAXIMUM EXTENT ALLOWABLE BY LAW.** Customer misuse including negligence, physical, or chemical abuse is not covered by this warranty. Installation defects are not covered by this warranty. All warranty claims must be reported immediately. Failure to report any warranty claim within 30 days of defect discovery will void this warranty. All products must be inspected prior to installation. Visual defects or nonconformities apparent prior to installation voids this warranty.

Tile is subject to variation in technical specifications, including DCOF, due to inherent variability in the raw materials and production process. Express technical specifications are not guarantees of minimum or maximum thresholds of performance. Tile containing abrasives create a rough surface, creating cleaning challenges because dirt and other contaminants lodge in the surface. Extra attention is necessary to ensure contaminants are removed promptly. Unless specifically stated otherwise, tile recommended for floor or wall applications refers to interior applications only. Daltile does not recommend its products for use on ceilings or roofs. Local building codes may dictate minimum tile performance specifications. Daltile does not warrant product installations that violate building codes. Photographic color images may not be an exact product match. Product samples are representative only. Express color match warranties are only extended to actual product samples.

Other Daltile Warranties

Implied Warranties Limited in Duration and Scope

Any implied warranty applicable to the product sale, including the implied warranty of merchantability or the implied warranty of fitness for a particular purpose is limited in duration to the duration of this written warranty or the maximum statutory period, whichever is less. Some states do not allow limitations on implied warranty duration, so the above limitation may not apply to you.

The Federal Magnuson-Moss Warranty Act limits disclaimers of implied warranties involving consumer products. To the maximum extent allowable by federal and state law, this warranty supplements or supersedes federal and state consumer goods warranty protections.

Implied Warranty of Fitness for a Particular Purpose

Daltile provides detailed information in its product literature with regard to appropriate tile and stone applications. In these specified applications, Daltile limits the duration of the implied warranty of fitness for a particular purpose to one year or the maximum statutory period prescribed by law, whichever is less. Failure to comply with recommended applications voids this warranty.

Natural stone products are mined and cut from natural formations. Because these products are not subject to a manufacturing process, quality warranties are limited to the specified representations in product literature and guidelines established by the Marble Institute of America. Daltile does not

warrant natural stone products for shade, size, thickness, warping, cleft variations, surface finish variations, or other natural variances on stone products.

Remedy Limitation and Disclaimer

If a defect in materials or workmanship is discovered within the one-year period, Daltile will either refund the price of the product or provide a replacement product after a reasonable number of attempts to remedy product defects. Buyer's remedy is limited to replacement or repair of the defective product. No consequential (including, but not limited to, lost profits) or incidental damages are recoverable. Daltile disclaims all express warranties not contained in this limited express warranty. Any representations made in connection with the sale of this product that differs from the terms of this warranty are not valid and should be brought to the attention of Daltile immediately (1-800-933-TILE).

Legal Notice: Warning Tile and installation products contain chemicals known to the state of California to cause cancer, birth defects, reproductive harm, respiratory harm or other health problems. For more product-specific information on chemical content, obtain an MSDS at Daltile.com or contact Daltile at 1-800-833-TILE.

To Make a Claim

1. The original purchaser must notify a Daltile Sales Service Center or an authorized representative in writing within 30 days of the occurrence of any defect.
2. After notification, Daltile or an authorized representative will inspect and/or test the product for defect and complete a Product Claim Action form. No claim will be honored without product inspection by Daltile or an authorized representative.
3. Upon determination that the product defect claim is valid, Daltile will notify the purchaser in writing. Daltile reserves the right to repair, replace or refund the originally purchased product, at its sole discretion.

PRODUCT DESCRIPTION

MAC-Guard[™] MAC-925 Topcoat is a 100% reactive, acrylic resin based on methyl-methacrylate (MMA) that cures in one hour. MAC-925 is designed to be applied as a clear final layer of a Res-Tek flooring system. MAC-925 has a low viscosity and provides a high degree of protection from mechanical abrasion, chemicals, and UV light.

TYPICAL USES

MAC-Guard MAC-925 Topcoat is applied neat over a Res-Tek self-leveling (SL), colored quartz (CQ) or colored flake (CF) floor as the last coat of the system. It is typically applied in two coats @ 15-20 mils/coat. The first coat protects the entire system by locking in broadcast media, while the second coat provides the first line of defense against water, chemicals, UV light, and other contaminants.

PHYSICAL CHARACTERISTICS

Viscosity (ASTM D2196, cPs): 38-48

Density (ASTM D1475, lbs/gal.): 8.16

Tensile Strength (ASTM D638, psi): 3,850

Shore D Hardness (ASTM D2240): 85

Coefficient of Thermal Expansion (ASTM D696, in./in./°F): 0.000035

Water Vapor Transmission (DIN53122, g/cm-hr-mmHg x 10⁻⁹): 1.43

Water Absorption (ASTM D570, wt.%): .05

Electrical Resistivity (ASTM D257):

Volume Resistance (ohm-cm): 10¹⁵

Surface Resistance (ohm): 10¹²

Pot Life: 15-20 minutes

Cure Time: 45-60 minutes

Shelf Life: Minimum 1 year from ship date (unopened)

DOT Classification: Flammable Liquid, Class 3, UN 186

PROPERTIES

- Chemically bonds to other MAC-Guard system components.
- Low viscosity makes for easy application with a roller or brush.
- UV stable.
- Cures in one hour.
- Cures at temperatures ranging from -15°F - 100°F.
- 100% reactive — VOC compliant.
- Excellent chemical, mechanical, scratch resistance

APPLICATION OF MATERIALS

MAC-Guard MAC-925 Topcoat is applied at a rate of 80-120 sq. ft. per gallon depending on system surface profile, using a medium nap roller or brush.

It is necessary to follow the mix ratios found in the MAC-Guard Dosing Chart.

RES-TEK INC.

110 Riverside Drive
Cartersville, Georgia 30120
P. 888.ResTek1 (888.737.8351)
F. 770.427.4037



MAC-Guard™

MAC-925

Topcoat

SURFACE PREPARATION

Once the previous coat has fully cured and excess media has been removed, topcoats may be applied. When applying over a flake system it is necessary to sand between topcoats. If following a different application schedule, please contact your Res-Tek representative.

STANDARD PACKAGING

MAC-Guard MAC-925 Topcoat is packaged in 38 lb pails and 400 lb drums. Powder Hardener (RT-BPO-50) is available in 10 lb containers and 55 lb boxes.

These products are sold by weight, not by volume. Product properties require that containers provided are not completely filled. See price sheet for actual container weight and volume.

STORAGE CONDITIONS

Store material in a cool and dry place out of direct sunlight. Do not store near open flame or ignition source. Read and understand all product labels and SDS sheets prior to use.

CAUTION

MAC-Guard MAC-925 Topcoat is a flammable liquid in its uncured state (as provided). All sources of ignition should be removed from the work area before handling this product. No smoking, open flames, or sparks should be permitted in and around the work area. Workers should wear protective clothing including goggles and impermeable gloves. If allowable exposure limits are exceeded, organic vapor respirators should be worn. All on-site personnel should become familiar with the SDS and hazard section of application binder in order to increase hazards awareness.

WARRANTY

Res-Tek Inc. warrants that materials shipped to buyers are free of any defects in material or workmanship according to Res-Tek's published data if used in accordance with Res-Tek's specified application procedure. Res-Tek Inc. shall not be responsible for any claim resulting from failure to utilize product in the manner in which it was intended, and in accordance with Res-Tek's application guidelines. Res-Tek Inc. has no responsibility for application and processing of products.

RES-TEK INC.

110 Riverside Drive
Cartersville, Georgia 30120
P. 888.ResTek-1 (888.737.8351)
F. 770.427.4037

